

## Declaration of conformity

for acid-resistant epoxy adhesive and joint grouting compound

### KEMAPOX LF

2-component acid-resistant epoxy adhesive and joint grouting compound for joints between 3-10 mm wide. For adhesion and joint grouting of floor and wall tiles in interiors and exteriors. It is used in food industry and chemical industry, for protection of tiling ponds, in hospitals, for swimming pools and sanitation, for terraces and balconies and underfloor heating and declared with technical properties from technical data sheet.

**Manufacturer and the authorized representative established within the European Economic Area:**

KEMA Puconci d.o.o.  
Puconci 109  
9201 Puconci  
SLOVENIJA

herewith declare that the product **KEMAPOX LF**

produced in the factory »15« are in accordance with the requirements of the enclosed ZA of the norms EN 12004:2007 for following regulations:

REACTION RESIN ADHESIVES FOR LAYING FLOOR AND WALL TILES IN INTERIORS AND EXTERIORS			
PRODUCT NAME	LIST OF THE FUNDAMENTAL CHARACTERISTICS AND STANDARDS		
	Initial shear adhesion strength  EN 12003 section 7.3	Shear adhesion strength after immersion in water  EN 12003 section 7.4	Shear adhesion strength after thermal shock  EN 12003 section 7.5
<b>KEMAPOX LF</b>	R2T	R2T	R2T

The tests were done by:

AIDICO, Istituto Tecnologico de la Construcción  Valencia, Parque Tecnológico.  Avda. Benjamin Franklin, 17  Apdo. 98. 46980, Paterna, Valencia - Espana  Organismo Notificado N° 1170	ITC – CNR  Istituto per le Tecnologie della Costruzione del Consiglio Nazionale delle Ricerche  Via Lombardia, 49 - 20098 San Giuliano Milanese – MI – Italy  Organismo Notificato N° 0970
--	--

And is controlled in accordance with existent foreign and national standards framed within internal quality control of production.

Puconci, 24.02.2012

Mark

Development and Quality director

Stanko Polajner, BSc

  
**KEMA Puconci d.o.o.**