

EC Declaration of conformity

for mineral dry shake surface hardener

TAL M KORUND 3

Dry shake-blend of hard minerals for surface beneficiation of fresh industrial concrete floors and screeds. Mineral dry-shake improves the mechanical properties and wears resistance of the surface of fresh industrial concrete floor or screed. For finishing of concrete floors with increased wear resistance and thickened (non-cavernous) surface.

Manufacturer and the authorized representative established within the European Economic Area:

KEMA Puconci d.o.o.
Puconci 109
9201 Puconci
SLOVENIJA

herewith declare that the product TAL M KORUND 3

is in conformity with the provisions of the following EC Directive(s) when installed in accordance with the installation instructions contained in the product documentation:

89/106/EEC Construction Products Directive

and that the standard referenced below have been applied:

EN 13813:2003

In accordance with Initial Type Test:

No. PTP-10/179

Issued by:

Development laboratory KEMA Puconci d.o.o., Puconci 109, 9201 Puconci, Slovenia

and complies the requirements for setting up the CE mark from table ZA 1.1, standard EN 13813:2003.

Product is submitted to factory production control according to standard EN 13813:2003.

The product is classified as C50-F7-A6 in class according to EN 13813:2003.

Puconci, 10.06.2011

Mark

Development and quality director
Stanko Polajner, B.S.C.



KEMA Puconci d.o.o.