

## EC Declaration of conformity

for mineral dry shake surface hardener

### TAL M KVARC

Dry shake-blend of hard minerals for surface beneficiation of fresh industrial concrete floors and screeds. Mineral dry-shake improves the mechanical properties and wears resistance of the surface of fresh industrial concrete floor or screed. For finishing of concrete floors with increased wear resistance and thickened (non-cavernous) surface.

Manufacturer and the authorized representative established within the European Economic Area:

KEMA Puconci d.o.o.  
Puconci 109  
9201 Puconci  
SLOVENIJA

herewith declare that the product TAL M KVARC

is in conformity with the provisions of the following EC Directive(s) when installed in accordance with the installation instructions contained in the product documentation:

#### **89/106/EEC Construction Products Directive**

and that the standard referenced below have been applied:

**EN 13813:2003**

In accordance with Initial Type Test:

**No. PTP-10/178**

Issued by:

Development laboratory KEMA Puconci d.o.o., Puconci 109, 9201 Puconci, Slovenia

and complies the requirements for setting up the CE mark from table ZA 1.1, standard EN 13813:2003.

Product is submitted to factory production control according to standard EN 13813:2003.

The product is classified as C40-F7-A9 in class according to EN 13813:2003.

Puconci, 10.06.2011

Mark

Development and quality director  
Stanko Polajner, B.S.C.



**KEMA Puconci d.o.o.**