

EC Declaration of conformity

for mineral dry shake for concrete floor finishing

TAL M STRONG

Dry shake-blend of hard minerals for surface beneficiation of fresh industrial concrete floors and screeds. Mineral dry-shake improves the mechanical properties and wears resistance of the surface of fresh industrial concrete floor or screed. For concrete floors exposed to combined loads (rolling, abrasion, blows).

Manufacturer and the authorized representative established within the European Economic Area:

KEMA Puconci d.o.o.

Puconci 109

9201 Puconci

SLOVENIJA

herewith declare that the product TAL M STRONG

is in conformity with the provisions of the following EC Directive(s) when installed in accordance with the installation instructions contained in the product documentation:

89/106/EEC Construction Products Directive

and that the standard referenced below have been applied:

EN 13813:2003

In accordance with Initial Type Test:

No. PTP-10/180

Issued by:

Development laboratory KEMA Puconci d.o.o., Puconci 109, 9201 Puconci, Slovenia

and complies the requirements for setting up the CE mark from table ZA 1.1, standard EN 13813:2003.

Product is submitted to factory production control according to standard EN 13813:2003.

The product is classified as C50-F7-A3 in class according to EN 13813:2003.

Puconci, 10.06.2011

Mark

Development and quality director
Stanko Polajner, B.S.C.



KEMA Puconci d.o.o.